

product type designation



Figure similar

RUGGEDCOM SFP1121-1FX2

RUGGEDCOM Accessory, SFP, 1 X 100MBIT/S, 100BASE-FX, LC-Interface, Optical: Multi Mode Fiber Optic up to max. 2km, 1310nm, -40...+85 Degrees Celsius

product brand name

RUGGEDCOM

Technical Product Detail Page

<https://i.siemens.com/1P6GK6000-8FE51-0AA0>

suitability for operation

compatible to RUGGEDCOM products with SFP-Slot

interfaces

number of electrical/optical connections / for network components or terminal equipment / maximum	1
number of optical interfaces / for network components or terminal equipment / maximum	1
number of 100 Mbit/s LC ports	1
design of the optical interface / for network components or terminal equipment	LC
range / at the optical interface / depending on the optical fiber used	2 km

ambient conditions

ambient temperature

- during operation
- during storage
- during transport
- note

-40 ... +85 °C
-40 ... +85 °C
-40 ... +85 °C
A maximum operating temperature of +85 °C is permissible for a duration of 16 hours

relative humidity / at 25 °C / without condensation / during operation / maximum

95 %

design, dimensions and weights

design	SFP Module
width	14 mm
height	9 mm
depth	57 mm
net weight	0.01 kg
product feature / conformal coating	No
fastening method	latched

standards, specifications, approvals

standard

- for safety / from CSA and UL
- for emitted interference
- for interference immunity

UL 60950-1, CSA C22.2 No. 60950-7
EN 61000-6-4 (Class A)
EN 61000-6-2

laser protection class

21 CFR Chapter 1, Subchapter J

certificate of suitability

- CE marking
- C-Tick

EN 61000-6-2, EN 61000-6-10
Yes
No

- KC approval
- E1 approval
- IEC 61850-3

No
No
Yes

further information / internet links

internet link

- to website: Selection guide for cables and connectors
- to website: Industry Mall/RUGGEDCOM selector
- to website: Industrial communication
- to website: Siemens RUGGEDCOM
- to web page: SiePortal
- to website: Image database
- to website: CAX-Download-Manager
- to website: Industry Online Support

<https://support.industry.siemens.com/cs/ww/en/view/109766358>
<https://www.siemens.com/ruggedcom-selector>
<https://www.siemens.com/simatic-net>
<https://www.siemens.com/ruggedcom>
<https://sieportal.siemens.com/>
<https://www.automation.siemens.com/bilddb>
<https://www.siemens.com/cax>
<https://support.industry.siemens.com>

security information

security information

Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement - and continuously maintain - a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under <https://www.siemens.com/cert>. (V4.7)

Approvals / Certificates

General Product Approval

other

[Manufacturer Declaration](#)



[inspection certificate](#)

[Miscellaneous](#)

last modified:

3/10/2026